

**Componenti / Adattatori**  
**Components / Adaptors**  
**Komponenten / Adapter**


**Adattatore a 90° maschio - BSP cilindrico 60° - Maschio BSP conico**

90° Adaptor BSP cylindrical - Male 60° - BSP tapered Male

90° Adapter BSP Aussengewinde - Zylindrisch 60° - BSP konisch

**F 90**

**ISO 8434-6**



<b>CODICE</b> Part n° Bestell. nr.	<b>Filetto</b> Thread Gewinde	<b>Ø A</b> ø A ø A	<b>Filetto</b> Thread Gewinde	<b>Ø B</b> ø B ø B	<b>CH</b>	<b>H</b>	<b>E</b>	<b>C</b>	<b>Pressione</b> Pression Druck
S 10 900 000 106 206	<b>R 1/4"</b>		G 1/4"		14	25	26	6	PN400
S 10 900 000 110 210	<b>R 3/8"</b>		G 3/8"		17	26	29	8	PN400
S 10 900 000 113 213	<b>R 1/2"</b>		G 1/2"		19	30	31	11	PN350
S 10 900 000 119 219	<b>R 3/4"</b>		G 3/4"		27	37	42	16	PN315
S 10 900 000 125 225	<b>R 1"</b>		G 1"		36	43	47	22	PN250
S 10 900 000 132 232	<b>R 1 1/4"</b>		G 1 1/4"		41	50	54	28	PN210


**Adattatore a T - Maschio BSP cilindrico 60°**

T Adaptor - BSP cylindrical Male 60°

T Adapter - BSP zylindrisch Aussengewinde 60°

**F 92**

**ISO 8434-6**



S 10 920 000 106 000	<b>G 1/4"</b>		G 1/4"		14	25	50	6	PN400
S 10 920 000 110 000	<b>G 3/8"</b>		G 3/8"		17	26	52	8	PN400
S 10 920 000 113 000	<b>G 1/2"</b>		G 1/2"		19	30	60	11	PN350
S 10 920 000 119 000	<b>G 3/4"</b>		G 3/4"		27	37	74	16	PN315
S 10 920 000 125 000	<b>G 1"</b>		G 1"		36	43	86	22	PN250


**Passaparatia BSP sede 60°**

Straight bulkhead connector BSP

Schottverbinder gerade BSP

**F 93**

**ISO 8434-6**



S 10 930 000 106 000	<b>G 1/4"</b>		G 1/4"		19	28	46	4,7	PN400
S 10 930 000 110 000	<b>G 3/8"</b>		G 3/8"		22	32	52	7,9	PN400
S 10 930 000 113 000	<b>G 1/2"</b>		G 1/2"		27	35	59	11,1	PN350
S 10 930 000 119 000	<b>G 3/4"</b>		G 3/4"		32	38	66	16,7	PN315
S 10 930 000 125 000	<b>G 1"</b>		G 1"		41	41	75	22,2	PN250
S 10 930 000 132 000	<b>G 1 1/4"</b>		G 1 1/4"		50	44	83	28,6	PN210
S 10 930 000 138 000	<b>G 1 1/2"</b>		G 1 1/2"		55	48	93	33,3	PN185


**F 343**

**Controdado BSP**

Hexagonal nut BSP

Gegenmutter BSP

**ISO 8434-6**



S 32 143 106 000	<b>G 1/4"</b>				19	6			
S 32 143 110 000	<b>G 3/8"</b>				22	7			
S 32 143 113 000	<b>G 1/2"</b>				27	8			
S 32 143 119 000	<b>G 3/4"</b>				32	9			
S 32 143 125 000	<b>G 1"</b>				41	10			
S 32 143 132 000	<b>G 1 1/4"</b>				50	13			
S 32 143 138 000	<b>G 1 1/2"</b>				55	15			