

fitting with test coupling series M16x2




fig. 1




fig. 2




fig. 3




fig. 4

type DKO

test coupling with 24° taper adapter (DIN3865 / ISO8434-1)

type BE

test coupling for compression ring fittings

type	PN	tube ØD	h1	h2	h3	h4	SW1	SW2	G	type DKO part number	fig.	type BE part number	fig.
L	315	6	53	-	20	39	14	17	M12x1,5	1-Z08-00-10-600-CF	1	1-Z09-00-00-601-CF	3
		8	53	-	20	39	17	17	M14x1,5	1-Z08-02-10-600-CF	1	1-Z09-02-00-601-CF	3
		10	50	-	22	37	19	17	M16x1,5	1-Z08-04-10-600-CF	1	1-Z09-04-00-601-CF	3
		12	50	-	22	37	22	17	M18x1,5	1-Z08-06-10-600-CF	1	1-Z09-06-00-601-CF	3
		15	51	-	22	37	27	19	M22x1,5	1-Z08-09-00-600-CF	1	1-Z09-09-00-601-CF	3
		18	-	22	28	-	32	-	M26x1,5	1-Z08-11-00-600-CF	2	1-Z09-11-00-601-CF	4
	160	22	-	22	30	-	36	-	M30x2	1-Z08-13-00-600-CF	2	1-Z09-13-00-601-CF	4
		28	-	24	32	-	41	-	M36x2	1-Z08-15-00-600-CF	2	1-Z09-15-00-601-CF	4
		35	-	27	42	-	50	-	M45x2	1-Z08-17-00-600-CF	2	1-Z09-17-00-601-CF	4
		42	-	28	45	-	60	-	M52x2	1-Z08-19-00-600-CF	2	1-Z09-19-00-601-CF	4
S	630	6	54	-	20	39	17	17	M14x1,5	1-Z08-01-10-600-CF	1	1-Z09-00-00-601-CF	3
		8	51	-	20	39	19	17	M16x1,5	1-Z08-03-10-600-CF	1	1-Z09-02-00-601-CF	3
		10	51	-	22	37	22	17	M18x1,5	1-Z08-05-10-600-CF	1	1-Z09-04-00-601-CF	3
		12	51	-	22	37	24	17	M20x1,5	1-Z08-07-10-600-CF	1	1-Z09-06-00-601-CF	3
		14	-	24	22	37	27	-	M22x1,5	1-Z08-08-00-600-CF	1	1-Z09-08-00-601-CF	3
		16	-	20	28	37	30	-	M24x1,5	1-Z08-10-00-600-CF	2	1-Z09-10-00-601-CF	3
	400	20	-	25	30	-	36	-	M30x2	1-Z08-12-00-600-CF	2	1-Z09-12-00-601-CF	4
		25	-	27	36	-	46	-	M36x2	1-Z08-14-00-600-CF	2	1-Z09-14-00-601-CF	4
		30	-	29	41	-	50	-	M42x2	1-Z08-16-00-600-CF	2	1-Z09-16-00-601-CF	4
		315	38	-	32	48	-	60	M52x2	1-Z08-18-00-600-CF	2	1-Z09-18-00-601-CF	4


For metal cap type A (universal) with vibration security
For metal cap type B (round) **without vibration security**
For metal cap type A (universal) **without vibration security**
For plastic cap type A (universal) **with vibration security**

Design with sealings made of FKM

replace 600 by 590
replace 600 by 020
replace 600 by 010
replace 600 by 100
replace 10 by 12
or replace 00 by 02

replace 601 by 591
replace 601 by 021
replace 601 by 011
replace 601 by 101
replace 00-601 by 02-601

90° fitting type BE with test coupling series M16x2



tube ØD	L1	L2	SW	h	part number (NBR)	part number (FKM)
8	20	37	22	59	1-Z80-03-60-080-CF	1-Z80-03-60-081-CF
10	20	37	22	59	1-Z80-05-60-120-CF	1-Z80-05-60-121-CF

For metal cap type A (universal) with vibration security replace 60 by
For metal cap type B (round) **without vibration security** replace 60 by
For metal cap type A (universal) **without vibration security** replace 60 by
For plastic cap type A (universal) **with vibration security** replace 60 by

59
02
01
10

Other dimensions on request. We reserve the right to change the technical performance. All dimensions in mm.