



**fitting with test coupling  
series M16x2**



**type GE**

(DIN2353 / ISO8434-1 and -4)



**type DKOGE**

(DIN2353 / ISO8434-1 and -4)

| type | PN  | tube ØD | G       | SW1 | SW2 | h  | L  | SW3          | SW4 | type GE<br>part number | type DKOGE<br>part number |
|------|-----|---------|---------|-----|-----|----|----|--------------|-----|------------------------|---------------------------|
| L    | 315 | 6       | M12x1,5 | 14  | 22  | 48 | 43 | 14           | 24  | 1-Z10-00-00-600-CF     | 1-Z10-20-00-601-CF        |
|      |     | 8       | M14x1,5 | 17  | 24  | 49 | 43 | 17           | 24  | 1-Z10-02-00-600-CF     | 1-Z10-22-00-601-CF        |
|      |     | 10      | M16x1,5 | 19  | 24  | 49 | 45 | 19           | 24  | 1-Z10-04-00-600-CF     | 1-Z10-24-00-601-CF        |
|      |     | 12      | M18x1,5 | 22  | 27  | 51 | 41 | 22           | 27  | 1-Z10-06-00-600-CF     | 1-Z10-26-00-601-CF        |
|      |     | 15      | M22x1,5 | 27  | 30  | 53 | 43 | 27           | 30  | 1-Z10-09-00-600-CF     | 1-Z10-29-00-601-CF        |
|      |     | 18      | M26x1,5 | 32  | 32  | 53 | 54 | 32           | 32  | 1-Z10-11-00-600-CF     | 1-Z10-31-00-601-CF        |
|      | 160 | 22      | M30x2   | 36  | 36  | 55 | 57 | 36           | 36  | 1-Z10-13-00-600-CF     | 1-Z10-33-00-601-CF        |
|      |     | 28      | M36x2   | 41  | 41  | 58 |    | upon request |     | 1-Z10-15-00-600-CF     | 1-Z10-35-00-601-CF        |
|      |     | 35      | M45x2   | 50  | 46  | 60 |    | upon request |     | 1-Z10-17-00-600-CF     | 1-Z10-37-00-601-CF        |
|      |     | 42      | M52x2   | 60  | 55  | 65 |    | upon request |     | 1-Z10-19-00-600-CF     | 1-Z10-39-00-601-CF        |
| S    | 630 | 6       | M14x1,5 | 17  | 24  | 49 | 46 | 17           | 24  | 1-Z10-01-00-600-CF     | 1-Z10-21-00-601-CF        |
|      |     | 8       | M16x1,5 | 19  | 24  | 49 | 47 | 19           | 24  | 1-Z10-03-00-600-CF     | 1-Z10-23-00-601-CF        |
|      |     | 10      | M18x1,5 | 22  | 24  | 49 | 48 | 22           | 24  | 1-Z10-05-00-600-CF     | 1-Z10-25-00-601-CF        |
|      |     | 12      | M20x1,5 | 24  | 24  | 49 | 47 | 24           | 24  | 1-Z10-07-00-600-CF     | 1-Z10-27-00-601-CF        |
|      |     | 14      | M22x1,5 | 27  | 27  | 51 | 50 | 27           | 27  | 1-Z10-08-00-600-CF     | 1-Z10-28-00-601-CF        |
|      |     | 16      | M24x1,5 | 30  | 30  | 52 | 55 | 30           | 30  | 1-Z10-10-00-600-CF     | 1-Z10-30-00-601-CF        |
|      | 400 | 20      | M30x2   | 36  | 32  | 53 | 62 | 36           | 36  | 1-Z10-12-00-600-CF     | 1-Z10-32-00-601-CF        |
|      |     | 25      | M36x2   | 46  | 41  | 58 | 62 | 46           | 41  | 1-Z10-14-00-600-CF     | 1-Z10-34-00-601-CF        |
|      |     | 30      | M42x2   | 50  | 46  | 60 |    | upon request |     | 1-Z10-16-00-600-CF     | 1-Z10-36-00-601-CF        |
|      |     | 38      | M52x2   | 60  | 55  | 65 |    | upon request |     | 1-Z10-18-00-600-CF     | 1-Z10-38-00-601-CF        |

For metal cap type A (universal) with vibration security

replace 600 by 590

replace 601 by 591

For metal cap type B (round) **without vibration security**

replace 600 by 020

replace 601 by 021

For metal cap type A (universal) **without vibration security**

replace 600 by 010

replace 601 by 011

For plastic cap type A (universal) **with vibration security**

replace 600 by 100


replace 601 by 101

Design with sealings made of FKM

replace 00-600 by 02-600

replace 00-601 by 02-601

**test coupling with 60° sealing cone (DKR)  
series M16x2**



| G     | h  | SW1 | SW2 | part number (NBR)  | part number (FKM)  |
|-------|----|-----|-----|--------------------|--------------------|
| G 1/4 | 54 | 19  | 17  | 1-Z08-76-00-600-CF | 1-Z08-76-02-600-CF |

For metal cap type A (universal) with vibration security

590

590

For metal cap type B (round) **without vibration security**

020

020

For metal cap type A (universal) **without vibration security**

010

010

For plastic cap type A (universal) **with vibration security**

100

100

**Other dimensions on request. We reserve the right to change the technical performance. All dimensions in mm.**