


# DIN 24° BLACKING PLUG

TAPPO FEMMINA GIREVOLE CONO A 24°  
BOUCHON DE FERMETURE AVEC O-RING DIN 24°  
VERSCHLUSSKEGEL MIT O-RING DIN 24°  
TAPÓN DE CIERRE CON JUNTA TÓRICA



| Code     | Thread | Dimensions |    |      | Pressure |      | Series |
|----------|--------|------------|----|------|----------|------|--------|
|          |        | D          | D1 | L1   | Bar      | Psi  |        |
|          |        | mm         | mm | mm   |          |      | L/S    |
| ATFGE06L |        | 6          | 6  | 18,5 | 315      | 4568 | L      |
| ATFGE08L |        | 8          | 8  | 18,5 | 315      | 4568 | L      |
| ATFGE10L |        | 10         | 10 | 20   | 315      | 4568 | L      |
| ATFGE12L |        | 12         | 12 | 20,5 | 315      | 4568 | L      |
| ATFGE15L |        | 15         | 15 | 20,5 | 315      | 4568 | L      |
| ATFGE18L |        | 18         | 18 | 22,5 | 315      | 4568 | L      |
| ATFGE22L |        | 22         | 22 | 25   | 160      | 2320 | L      |
| ATFGE28L |        | 28         | 28 | 25,5 | 160      | 2320 | L      |
| ATFGE35L |        | 35         | 35 | 30   | 160      | 2320 | L      |
| ATFGE42L |        | 42         | 42 | 30   | 160      | 2320 | L      |
| ATFGE06S |        | 6          | 6  | 18,5 | 630      | 9137 | S      |
| ATFGE08S |        | 8          | 8  | 18,5 | 630      | 9137 | S      |
| ATFGE10S |        | 10         | 10 | 20   | 630      | 9137 | S      |
| ATFGE12S |        | 12         | 12 | 20,5 | 630      | 9137 | S      |
| ATFGE14S |        | 14         | 14 | 22,5 | 630      | 9137 | S      |
| ATFGE16S |        | 16         | 16 | 23,5 | 400      | 5801 | S      |
| ATFGE20S |        | 20         | 20 | 28,5 | 400      | 5801 | S      |
| ATFGE25S |        | 25         | 25 | 29   | 400      | 5801 | S      |
| ATFGE30S |        | 30         | 30 | 30,5 | 400      | 5801 | S      |
| ATFGE38S |        | 38         | 38 | 33   | 315      | 4568 | S      |