


VSD...

VSD... -1.4571



						Blanking plugs VSD ...	Blanking plugs Stainless steel (1.4571) VSD ... -1.4571
Series	PN bar (psi)	Tube outer diameter	Model	Best-Nr.	kg/100 pc.	Part no.	Part no.
LL	100 (1450)	4	VSD 4 LL M.MB.	WAL612327	0,2	WAL612327	WAL618772
		6	VSD 6 LL M.MB.	WAL612328	0,4	WAL612328	WAL618773
		8	VSD 8 LL M.MB.	WAL612329	0,7	WAL612329	WAL618774
L	800 (11603)	6	VSD 6 L/S M.MB.	WAL612330	0,5	WAL612330	WAL618775
		8	VSD 8 L/S M.MB.	WAL612331	0,7	WAL612331	WAL618776
		10	VSD 10 L/S M.MB.	WAL612332	1,3	WAL612332	WAL618777
	630 (9137)	12	VSD 12 L/S M.MB.	WAL612333	1,8	WAL612333	WAL618778
	400 (5801)	15	VSD 15 L M.MB.	WAL612334	2,4	WAL612334	WAL618779
		18	VSD 18 L M.MB.	WAL612335	3,7	WAL612335	WAL618780
	250 (3626)	22	VSD 22 L M.MB.	WAL612336	5,5	WAL612336	WAL618781
		28	VSD 28 L M.MB.	WAL612337	7,9	WAL612337	WAL618782
		35	VSD 35 L M.MB.	WAL612338	16,4	WAL612338	WAL618783
		42	VSD 42 L M.MB.	WAL612339	23,4	WAL612339	WAL618784
	800 (11603)	6	VSD 6 L/S M.MB.	WAL612330	0,5	WAL612330	WAL618775
		8	VSD 8 L/S M.MB.	WAL612331	0,7	WAL612331	WAL618776
		10	VSD 10 L/S M.MB.	WAL612332	1,3	WAL612332	WAL618777
		12	VSD 12 L/S M.MB.	WAL612333	1,8	WAL612333	WAL618778
	630 (9137)	14	VSD 14 S M.MB.	WAL612340	2,7	WAL612340	WAL618785
		16	VSD 16 S M.MB.	WAL612341	3,5	WAL612341	WAL618786
		20	VSD 20 S M.MB.	WAL612342	6,5	WAL612342	WAL618787
S	420 (6091)	25	VSD 25 S M.MB.	WAL612343	10,6	WAL612343	WAL618788
		30	VSD 30 S M.MB.	WAL612344	16,4	WAL612344	WAL618789
		38	VSD 38 S M.MB.	WAL612345	28,0	WAL612345	WAL618790

⚠ Caution: The pressure specifications refer to the steel version. For the stainless steel version (1.4571), please refer to the pressure specifications on page B5.