


## VS-M ... -WD

### VS-M ... -WD-1.4571

- with hexagon socket
- with soft seal made from NBR\* (e.g. Perbunan) for steel
- with soft seal made from FKM (e.g. Viton) for stainless steel (1.4571)
- Metric stud type E to DIN EN ISO 9974-2



|                 |            |                        |                |    |      |    |    |           | Blanking ends<br>Stainless steel (1.4571)<br>VS-M ... -WD-1.4571 |
|-----------------|------------|------------------------|----------------|----|------|----|----|-----------|------------------------------------------------------------------|
| PN<br>bar (psi) | M          | Model                  | kg/<br>100 pc. | D  | L    | i  | S  | Part no.  | Part no.                                                         |
| 400 (5801)      | M 10 x 1   | VS-M 10 x 1 -WD        | 0.6            | 14 | 12   | 8  | 5  | WAL028302 | WAL605040                                                        |
|                 | M 12 x 1.5 | VS-M 12 x 1.5 -WD      | 1.1            | 17 | 17   | 12 | 6  | WAL028303 | WAL605042                                                        |
|                 | M 14 x 1.5 | VS-M 14 x 1.5 -WD      | 1.5            | 19 | 17   | 12 | 6  | WAL028304 | WAL374724                                                        |
|                 | M 16 x 1.5 | VS-M 16 x 1.5 -WD      | 1.8            | 22 | 17   | 12 | 8  | WAL028305 | WAL605044                                                        |
|                 | M 18 x 1.5 | VS-M 18 x 1.5 -WD      | 2.8            | 24 | 17   | 12 | 8  | WAL029844 | WAL604532                                                        |
|                 | M 20 x 1.5 | VS-M 20 x 1.5 -WD      | 3.6            | 26 | 19   | 14 | 10 | WAL028306 | WAL609395                                                        |
|                 | M 22 x 1.5 | VS-M 22 x 1.5 -WD      | 4.6            | 27 | 19   | 14 | 10 | WAL028307 | WAL374725                                                        |
|                 | M 26 x 1.5 | VS-M 26 x 1.5 -WD      | 7.2            | 32 | 21   | 16 | 12 | WAL028308 | WAL617296                                                        |
|                 | M 27 x 2   | VS-M 27 x 2 -WD        | 7.5            | 32 | 21   | 16 | 12 | WAL028309 | WAL605284                                                        |
| 250 (3626)      | M 33 x 2   | VS-M 33 x 2 -WD        | 11.8           | 40 | 22.5 | 16 | 17 | WAL028310 | WAL605143                                                        |
|                 | M 42 x 2   | VS-M 42 x 2 -WD        | 18.6           | 50 | 22.5 | 16 | 22 | WAL028311 | WAL617297                                                        |
|                 | M 48 x 2   | VS-M 48 x 2 -WD        | 24.7           | 55 | 22.5 | 16 | 24 | WAL028312 | WAL617298                                                        |
| 400 (5801)      | M 42 x 2   | VS-M 42 x 2 -WD/PN 400 | 28.3           | 50 | 28   | 20 | 22 | WAL608445 |                                                                  |
|                 | M 48 x 2   | VS-M 48 x 2 -WD/PN 400 | 39.2           | 55 | 30   | 22 | 24 | WAL608446 |                                                                  |

**⚠ Caution:** The pressure specifications refer to the steel version. For the stainless steel version (1.4571), please refer to the pressure specifications on page B5.

\*For FPM (e.g. Viton) see price list / available on request